

MATERIAL SAFETY DATA SHEET
AZ P4620 Photoresist (US)



Substance key: BBG70J7
Version 1

REVISION DATE: 07/05/2005
Print Date: 07/05/2005

Section 01 - Product Information

Identification of the company:	AZ Electronic Materials USA Corp. 70 Meister Avenue Somerville, NJ 08876 Telephone No.: 800-515-4164
	Information on the substance/preparation Product Safety: 908-429-3562
	Emergency Tel. number: 800-424-9300 CHEMTREC

Trade name: AZ P4620 Photoresist (US)

Section 02 - Composition information

Hazardous ingredients:

Chemical Name	CAS-no. (Trade secret no.)	Concentration [%]
1-Methoxy-2-propanol acetate	108-65-6	62.00

Non-hazardous ingredients:

Chemical Name	CAS-no. (Trade secret no.)	Concentration [%]
Cresol novolak resin	117520-84-0	< 35.00
Diazonaphthoquinonesulfonic esters	5610-94-6	< 5.00

Section 03 - Hazardous identification

Emergency overview: OSHA combustible liquid; DOT flammable liquid, Amber-red liquid with characteristic odor., Irritating on contact or inhalation, Partially dissolves in water leaving a floating viscous mass.

Expected route of entry

- Skin contact:** Causes skin irritation.
- Ingestion:** May be harmful if swallowed.
- Inhalation:** Single exposure unlikely to be hazardous, High vapor concentration causes irritation to the nose, throat, and lungs.
- Eye contact:** Causes eye irritation.

3005120

MATERIAL SAFETY DATA SHEET
AZ P4620 Photoresist (US)



Substance key: BBG70J7
Version 1

REVISION DATE: 07/05/2005
Print Date: 07/05/2005

Health effects of exposure:

Component information:

Eye: Causes eye irritation. Skin: Causes skin irritation. Ingestion: May be harmful if swallowed. Inhalation: Single exposure unlikely to be hazardous. High vapor concentration causes irritation to the nose, throat, and lungs. Systemic Effects: No hazard in normal industrial use. Reproductive & birth defects: Exposures having no adverse effect on the mother should have no effect on the fetus.

1-Methoxy-2-propanol acetate (108-65-6)

1-Methoxy-2-propanol acetate (PGMEA) can cause skin, eye, and respiratory irritation. Extreme or prolonged exposure may cause gastric and central nervous system effects. Long term, high level exposure to PGMEA has resulted in adverse effects to the livers and kidneys of experimental animals. PGMEA is readily absorbed through intact skin

Listed carcinogen: IARC: NO NTP: NO OSHA: NO

HMIS:

Health: 2 Flammability: 2 Reactivity: 0 Personal protection: X

NFPA:

Health: 2 Flammability: 2 Reactivity: 0 Special notice: NONE

Section 04 - First aid measures

After inhalation: Remove victim to fresh air. Consult physician if irritation occurs.

After contact with skin: Immediately remove contaminated clothing. Flush affected area thoroughly with water. After flushing with water, remove residue with soap and water. If necessary, clean area with a cloth or paper towel wetted with acetone. Assure adequate ventilation. Dispose of cloth/towel in a suitable receptacle. Consult physician if irritation occurs or if irritation is extensive

After contact with eyes: Flush thoroughly with water for 15 minutes. Get immediate medical help

After ingestion: If person is conscious, give water or milk to dilute stomach contents. Never give anything by mouth to an unconscious person. Consult physician.

Advice to doctor / Administer oxygen if there is difficulty in breathing.

MATERIAL SAFETY DATA SHEET
AZ P4620 Photoresist (US)



Substance key: BBG70J7
Version 1

REVISION DATE: 07/05/2005
Print Date: 07/05/2005

Treatment:

Section 05 - Fire fighting measures

Flash point:	38.00 °C Method: closed cup
Suitable extinguishing media:	Carbon dioxide, water, alcohol resistant foam, dry chemical.
Special fire fighting procedure:	Use self-contained breathing apparatus and full protective clothing. Use water spray to cool drums in fire area.
Specific hazards during fire fighting:	Thermal decomposition may generate carbon dioxide, carbon monoxide, and oxides of nitrogen and sulfur.
Unusual fire and explosion hazards:	Solvent vapors., Emits toxic fumes under fire conditions.

Section 06 - Accidental release measures

Steps to be taken in case of spill or leak:	Wearing appropriate personal protective equipment, contain spill, ventilate area of spill or leak, remove all sparking devices or ignition sources, collect onto inert absorbent, and place in a suitable container.
---	--

Section 07 - Handling and Storage

Advice on safe handling:

Keep away from heat and flame.
Wash thoroughly after handling.
Keep container closed.
Avoid breathing vapors and contact with skin, eyes, and clothing.
Use only with adequate ventilation and proper protective eyewear, gloves, and clothing.

Further information for storage conditions:

Store at appropriate temperature. See label for details.
Store in original container.
Transport and store under dry conditions tightly closed and protected from heat and light.
Pressure may build up slowly in closed containers due to gradual decomposition. This is accelerated by heat and light. May liberate combustible solvent vapors.

Section 08 - Exposure Control / personal protection

MATERIAL SAFETY DATA SHEET
AZ P4620 Photoresist (US)



Substance key: BBG70J7
Version 1

REVISION DATE: 07/05/2005
Print Date: 07/05/2005

Respiratory protection: Chemical cartridge respirator recommended for exposures exceeding TLV.

Eye protection: Safety eyewear to protect against splashes.

Skin and body protection: Clothing suitable to prevent skin contact.

Advice on system design: Use local exhaust ventilation.

Section 09 - Physical and chemical properties

Form: Liquid

Color: Clear, amber-red

Odor: Strong, characteristic odor.

Water solubility: The solvent is water soluble but the product forms two layers.

Starts to boil: 134 °C

Evaporation number: Reference substance: n-butyl acetate app.

Vapor pressure: 2.2 Torr

Viscosity, dynamic: approx. 520 mPas

Loss on drying: 62 %

Section 10 - Stability and reactivity

Hazardous reactions: Stable.

Hazardous polymerization: Will not occur.

Conditions to avoid: Avoid contact with oxidizing agents. Avoid contact with strong acids. Avoid contact with alkaline materials.

Section 11 - Toxicological information

Acute oral toxicity: Based on data from components this material is considered, not harmful (rat acute oral LD50 > 5000 mg/kg).

Acute inhalation toxicity: Based on data from components, this material is considered, not harmful (LC50 greater than 10,000 ppm or 200 mg/l).

MATERIAL SAFETY DATA SHEET
AZ P4620 Photoresist (US)



Substance key: BBG70J7
Version 1

REVISION DATE: 07/05/2005
Print Date: 07/05/2005

Based on component data, material is considered irritating to the respiratory tract.

- 1-Methoxy-2-propanol acetate (108-65-6)
Acute oral toxicity: LD50 rat (male)
8,500 mg/kg
- 1-Methoxy-2-propanol acetate (108-65-6)
Acute oral toxicity: LD50 rat (female)
10,000 mg/kg
- 1-Methoxy-2-propanol acetate (108-65-6)
Acute inhalation toxicity: LC50 rat
> 4350 ppm
- 1-Methoxy-2-propanol acetate (108-65-6)
Acute dermal toxicity: LD50 rabbit
> 5 mg/kg

Section 12 - Ecological information

- 1-Methoxy-2-propanol acetate (108-65-6)
Toxicity to fish: (Fathead minnow)
161 mg/l
- 1-Methoxy-2-propanol acetate (108-65-6)
Toxicity of aquatic invertebrates: (Daphnia magna)
400 mg/l

Section 13 - Disposal considerations

Product: Consult local, state, and federal regulations.
For disposal, this material is a flammable hazardous waste under RCRA.

Section 14 - Transport information

- Land transport
 - DOT: Not restricted
- Sea transport

MATERIAL SAFETY DATA SHEET
AZ P4620 Photoresist (US)



AZ Electronic Materials

Substance key: BBG70J7
Version 1

REVISION DATE: 07/05/2005
Print Date: 07/05/2005

▪ **IMDG:**

UN-No: 1993
Proper technical name: FLAMMABLE LIQUID, N.O.S. contains (2-Methoxy-1-methyl ethyl acetate)
Class: 3
Packaging group: III
Marine pollutant:
EmS: F-E, S-E
MFAG:
Labels: 3

Air transport

▪ **ICAO/IATA-DGR:**

UN/ID No.: UN 1993
Proper technical name: FLAMMABLE LIQUID, N.O.S. contains (2-Methoxy-1-methyl ethyl acetate)
Class: 3
Packaging group: III
Labels: 3

Section 15 - Regulatory information

TSCA Status: All components of this product are listed on the TSCA Inventory.

SARA 313 information: This product is not subject to SARA Title III Section 313 reporting requirements under 40 CFR 372

Volatile organic compounds: Content VOC (g/l): 620 g/l
Method: calculated

Section 16 - Other information

Label information

CAUTION!

COMBUSTIBLE LIQUID AND VAPOR HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN Contains material that, based on animal data, can cause skin, eye, and respiratory irritation. Prolonged or repeated overexposure may cause gastric and central nervous system effects.

MATERIAL SAFETY DATA SHEET
AZ P4620 Photoresist (US)



Substance key: BBG70J7
Version 1

REVISION DATE: 07/05/2005
Print Date: 07/05/2005

Keep away from heat and flame. Avoid breathing vapor. Avoid contact with skin, eyes, and clothing. Use only with adequate ventilation, and proper protective eyewear, gloves, and clothing. Wash thoroughly after handling. Keep container closed.

In case of contact, flush eyes with plenty of water for 15 minutes. Get medical attention immediately. Flush affected skin areas with water, and wash with mild soap and water. Remove contaminated clothing. If INHALED, remove individual to fresh air. If breathing is difficult, give oxygen. If ingested, give water or milk to dilute stomach contents. Never give anything by mouth to an unconscious person. Get medical attention immediately for ingestion or breathing problems or if skin contact is extensive.

In case of fire, use water, alcohol resistant foam, dry chemical, or CO₂.

If spilled, wear protective clothing, remove ignition sources, prevent sparks, and ventilate area. Absorb with inert material, collect, and place in a chemical waste container.

Keep sealed in original container. Product must be kept refrigerated until use. Temperature range for refrigeration is 30 to 55 F (1 to 13 C). Allow product to reach ambient temperature prior to use. Empty container may contain harmful residue.

The solvent in this product is not photochemically reactive per Rule 102 of the California South Coast Air Quality Management District.

This information is supplied under the OSHA Hazard Communication Standard, 29 CFR 1910.1200, and is offered in good faith based on data available to us that we believe to be true and accurate. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable to the material. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate for that use. No warranty, express or implied, is made regarding the accuracy of this data, the hazards connected with the use of the material, or the results to be obtained from the use thereof. We assume no responsibility for damage or injury from the use of the product described herein. Data provided here are typical and not intended for use as product specifications. (R) and TM indicate trademarks of AZ Electronic Materials USA Corp., its business partners and suppliers.
